

# Material Safety Data Sheet

## 24 Hour Emergency Phone Numbers:

**Medical: 1-800-327-3874**

**1-513-558-5111**

**Transportation:**

**1-800-535-5053**

**1-352-323-3500**

NOTE: National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

**IMPORTANT:** Provide this information to employees, customers, and users of this product. Read this MSDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this MSDS are further described in Section 16.

## Section 1 - Chemical Product / Company Information

This Material Safety Data Sheet is available in Canadian French and Hispanic American Spanish upon request.  
Esta hoja de datos de la seguridad de los materiales está disponible en francés canadiense y en español a su solicitud.  
Los Datos de Seguridad del Producto pueden obtenerse en Espanol si lo requiere.

**Product Name:** Alex Painters Acrylic Latex Caulk - All Colors **Revision Date:** 11/10/2004  
**Product UPC Number:** 18065 18609 18618 18670 30206 73625 73630 **Supercedes:** 10/29/2004  
**Product Use/Class:** Latex Caulk **MSDS Number:** 00010011001  
**Manufacturer:** DAP Inc.  
 2400 Boston Street Suite 200  
 Baltimore, MD 21224-4723  
 888-327-8477 (non-emergency matters)

## Section 2 - Composition / Information On Ingredients

| Chemical Name                  | CASRN           | WT%     | ACGIH TWA | ACGIH STEL | ACGIH CEIL | OSHA TWA                            | OSHA STEL | OSHA CEIL | Skin |
|--------------------------------|-----------------|---------|-----------|------------|------------|-------------------------------------|-----------|-----------|------|
| Calcium carbonate              | 1317-65-3       | 40-70   | 10 MGM3   | N.E.       | N.E.       | 5 MGM3                              | N.E.      | N.E.      | No   |
| Ester Branched & Linear(C7&C9) | PHTHALATE ESTER | 1-5     | N.E.      | N.E.       | N.E.       | N.E.                                | N.E.      | N.E.      | No   |
| Stoddard solvent               | 8052-41-3       | 0.5-1.5 | 100 PPM   | N.E.       | N.E.       | 500 PPM                             | N.E.      | N.E.      | No   |
| Ethylene glycol                | 107-21-1        | 0.1-1.0 | N.E.      | N.E.       | 100 MGM3   | N.E.                                | N.E.      | N.E.      | No   |
| Silica, crystalline            | 14808-60-7      | 0.1-1.0 | 0.05 MGM3 | N.E.       | N.E.       | (10 ÷ % SiO <sub>2</sub> ) / 2 MGM3 | N.E.      | N.E.      | No   |
| Titanium dioxide               | 13463-67-7      | 0.1-1.0 | 10 MGM3   | N.E.       | N.E.       | 15 MGM3                             | N.E.      | N.E.      | No   |
| Ammonia                        | 7664-41-7       | 0.1-1.0 | 25 PPM    | 35 PPM     | N.E.       | 50 PPM                              | N.E.      | N.E.      | No   |
| Formaldehyde                   | 50-00-0         | <0.02   | N.E.      | N.E.       | 0.3 PPM    | 0.75 PPM                            | 2 PPM     | N.E.      | No   |
| Ethyl acrylate                 | 140-88-5        | <0.008  | 5 PPM     | 15 PPM     | N.E.       | 25 PPM                              | N.E.      | N.E.      | Yes  |
| Acetaldehyde                   | 75-07-0         | <0.002  | N.E.      | N.E.       | 25 PPM     | 200 PPM                             | N.E.      | N.E.      | No   |
| Acrylonitrile                  | 107-13-1        | <0.0002 | 2 PPM     | N.E.       | N.E.       | 2 PPM                               | 10 PPM    | N.E.      | Yes  |

### Exposure Notes:

50-00-0 Formaldehyde is a specially regulated substance for which an OSHA chemical-specific exposure standard exists. Detailed information regarding this substance may be found in 29 CFR 1910.1048. Medical surveillance information regarding this substance may be found in Appendix C to 29 CFR 1910.1048.

107-13-1 Acrylonitrile is a specially regulated substance for which an OSHA chemical-specific

exposure standard exists. Detailed information regarding this substance may be found in 29 CFR 1910.1045. Medical surveillance information regarding this substance may be found in Appendix C to 29 CFR 1910.1045.

**Important:** Listed Permissible Exposure Levels (PEL) are from the U.S. Dept. of Labor OSHA Final Rule Limits (CFR 29 1910.1000); these limits may vary between states.

**Note:** An employee's skin exposure to substances having a "YES" in the "SKIN" column in the table above shall be prevented or reduced to the extent necessary under the circumstances through the use of gloves, coveralls, goggles or other appropriate personal protective equipment, engineering controls or work practices

### Section 3 - Hazards Identification

**Emergency Overview:** A colored paste with a very slight ammonia odor. **WARNING!** Harmful if swallowed or absorbed through the skin. May cause irritation to the respiratory tract. May cause eye, skin, nose, throat and respiratory tract irritation. This product contains ethylene glycol.

Refer to other MSDS sections for other detailed information.

**Effects Of Overexposure - Eye Contact:** May cause eye irritation.

**Effects Of Overexposure - Skin Contact:** Harmful if absorbed through the skin. May cause sensitization by skin contact. May cause skin irritation and/or dermatitis.

**Effects Of Overexposure - Inhalation:** Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. May cause irritation of respiratory tract. Inhalation of vapors may cause irritation of the nose, throat, lungs and respiratory tract. Prolonged, repeated, or high exposures may cause weakness and depression of the central nervous system.

**Effects Of Overexposure - Ingestion:** Harmful if swallowed.

**Effects Of Overexposure - Chronic Hazards:** Prolonged and repeated skin contact may cause irritation and possibly dermatitis. Repeated or prolonged exposure may cause respiratory system damage. Overexposure may cause kidney, cardiovascular, skin and liver damage. Formaldehyde vapor is a known animal carcinogen according to OSHA and NTP and is considered possibly carcinogenic to humans by inhalation. The International Agency for Research on Cancer considers formaldehyde to be a human carcinogen. Ethylene Glycol may cause kidney and liver damage upon prolonged and repeated overexposures. Studies have shown that repeated inhalation of ethylene glycol has produced adverse cardiovascular changes in laboratory animals. Ethylene glycol has been shown to cause birth defects in laboratory animals.

**Primary Route(s) Of Entry:** Skin Contact, Inhalation, Eye Contact

**Medical Conditions which May be Aggravated by Exposure:** None known.

### Section 4 - First Aid Measures

**First Aid - Eye Contact:** In case of contact, immediately flush eyes with large quantities of water for at least 15 minutes until irritation subsides. Get medical attention immediately.

**First Aid - Skin Contact:** Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical aid if symptoms persist. Remove and wash contaminated clothing.

**First Aid - Inhalation:** If inhaled, remove to fresh air. If breathing is difficult, leave the area to obtain fresh air. If continued breathing difficulty is experienced, get medical attention immediately.

**First Aid - Ingestion:** If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

**Note to Physician:** No Information.

**COMMENTS:** Call Medical Emergency at 1-800-327-3874 if any irritation or complication arise from any of the above routes of entry.

## Section 5 - Fire Fighting Measures

**Flash Point, F:** Greater than 200 degrees Fahrenheit

**Lower Explosive Limit, %:** Not Established

**Method:** (Seta Closed Cup)

**Upper Explosive Limit, %:** Not Established

**Extinguishing Media:** Carbon Dioxide, Dry Chemical, Foam, Water Fog

**Unusual Fire And Explosion Hazards:** No special protective measures against fire required.

**Special Firefighting Procedures:** Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

## Section 6 - Accidental Release Measures

**Steps To Be Taken If Material Is Released Or Spilled:** Wear proper protective equipment as specified in Section 8. Use absorbent material or scrape up dried material and place in container.

## Section 7 - Handling And Storage

**Handling:** KEEP OUT OF REACH OF CHILDREN! DO NOT TAKE INTERNALLY. Do not breathe vapors. Use only with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing. Open all windows and doors or use other means to ensure cross-ventilation and fresh air entry during application and drying. Odor is not an adequate warning for hazardous conditions. Wash thoroughly after handling.

**Storage:** Close container after each use. Store containers away from excessive heat and freezing. Store away from caustics and oxidizers. Do not store at temperatures above 120 degrees F.

## Section 8 - Exposure Controls / Personal Protection

**Precautionary Measures:** Please refer to other sections and subsections of this MSDS.

**Engineering Controls:** Good general ventilation should be sufficient to control airborne levels. Ensure adequate ventilation, especially in confined areas. Local ventilation of emission sources may be necessary to maintain ambient concentrations below recommended exposure limits.

**Respiratory Protection:** In case of insufficient ventilation, wear suitable respiratory equipment. A NIOSH-approved air purifying respirator with an organic vapor cartridge or canister may be necessary under certain circumstances where airborne concentrations are expected to exceed exposure limits. A respiratory protection program that meets the OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

**Skin Protection:** Rubber gloves.

**Eye Protection:** Goggles or safety glasses with side shields.

**Other protective equipment:** Not required under normal use.

**Hygienic Practices:** Remove and wash contaminated clothing before re-use. Wash hands before breaks and at the end of workday.

## Section 9 - Physical And Chemical Properties

|                                      |                     |                          |                             |
|--------------------------------------|---------------------|--------------------------|-----------------------------|
| <b>Boiling Range:</b>                | Not Established     | <b>Vapor Density:</b>    | Heavier Than Air            |
| <b>Odor:</b>                         | Very Slight Ammonia | <b>Odor Threshold:</b>   | Not Established             |
| <b>Appearance:</b>                   | Colored             | <b>Evaporation Rate:</b> | Slower Than n-Butyl Acetate |
| <b>Solubility in H<sub>2</sub>O:</b> | Not Established     | <b>Specific Gravity:</b> | 1.639                       |
| <b>Freeze Point:</b>                 | Not Established     | <b>pH:</b>               | Between 7.0 and 12.0        |
| <b>Vapor Pressure:</b>               | Not Established     | <b>Viscosity:</b>        | Not Established             |
| <b>Physical State:</b>               | Paste               |                          |                             |

When reported, vapor pressure of this product has been calculated theoretically based on its constituent makeup and has not been determined experimentally.

(See section 16 for abbreviation legend)

## Section 10 - Stability And Reactivity

**Conditions To Avoid:** Excessive heat and freezing.

**Incompatibility:** Incompatible with strong bases and oxidizing agents.

**Hazardous Decomposition Products:** Normal decomposition products, i.e., CO<sub>x</sub>, NO<sub>x</sub>.

**Hazardous Polymerization:** Hazardous polymerization will not occur under normal conditions.

**Stability:** Stable under recommended storage conditions.

## Section 11 - Toxicological Information

**Product LD<sub>50</sub>:** Not Established

**Product LC<sub>50</sub>:** Not Established

| CASRN           | Chemical Name                  | LD <sub>50</sub>   | LC <sub>50</sub>          | WT%     |
|-----------------|--------------------------------|--------------------|---------------------------|---------|
| PHTHALATE ESTER | Ester Branched & Linear(C7&C9) | Oral Rat: 10 mg/kg | -----                     | 1-5     |
| 107-21-1        | Ethylene glycol                | Rat:4700 mg/kg     | Rat:10876 mg/kg           | 0.1-1.0 |
| 7664-41-7       | Ammonia                        | -----              | Rat:2000 ppm/4H           | 0.1-1.0 |
| 50-00-0         | Formaldehyde                   | -----              | Rat:203 mg/m <sup>3</sup> | <0.02   |
| 140-88-5        | Ethyl acrylate                 | -----              | Rat:1414 ppm/4H           | <0.008  |
| 75-07-0         | Acetaldehyde                   | -----              | Rat:13300 ppm/4H          | <0.002  |
| 107-13-1        | Acrylonitrile                  | Oral Rat:78 mg/kg  | Rat:425 ppm/4H            | <0.0002 |

**Carcinogenicity:**

| CAS No.    | Chemical Name       | ACGIH   | OSHA                     | IARC   | NTP                     | WT%      |
|------------|---------------------|---|--------------------------|--|-------------------------|----------|
| 14808-60-7 | Silica, crystalline | Suspected human carcinogen.                                   | -----                    | -----  | Known carcinogen.       | 0.1-1.0  |
| 13463-67-7 | Titanium dioxide    | -----   | -----                    | Classification not possible from current data. | -----                   | 0.1-1.0  |
| 50-00-0    | Formaldehyde        | Suspected human carcinogen.                                   | Potential cancer hazard. | Human carcinogen.                              | Anticipated carcinogen. | <0.02    |
| 140-88-5   | Ethyl acrylate      | -----   | -----                    | Possible carcinogen.                           | -----                   | <0.008   |
| 75-07-0    | Acetaldehyde        | Confirmed animal carcinogen with unknown relevance to humans. | -----                    | Possible carcinogen.                           | Anticipated carcinogen. | <0.002   |
| 107-13-1   | Acrylonitrile       | Confirmed animal carcinogen with unknown relevance to humans. | Cancer hazard.           | Possible carcinogen.                           | Anticipated carcinogen. | <0.0002  |
| 79-06-1    | Acrylamide          | Confirmed animal carcinogen with unknown relevance to humans. | -----                    | Probable carcinogen.                           | Anticipated carcinogen. | <0.00005 |

|         |                |                             |                |                   |                   |           |
|---------|----------------|-----------------------------|----------------|-------------------|-------------------|-----------|
| 75-21-8 | Ethylene oxide | Suspected human carcinogen. | Cancer hazard. | Human carcinogen. | Known carcinogen. | <0.000006 |
|---------|----------------|-----------------------------|----------------|-------------------|-------------------|-----------|

**Significant Data with Possible Relevance to Humans:** This product contains trace amounts of free formaldehyde. OSHA and NTP identify formaldehyde as a potential carcinogen. IARC identifies formaldehyde as a human carcinogen. Formaldehyde has been shown to cause mutations in a variety of in-vitro test systems, the significance of which to humans is unknown. In a two-year inhalation study, rats showed carcinogenic effects in the respiratory system at 15 ppm of formaldehyde. There should be minimal risk when used with ventilation adequate to keep the atmospheric concentration of formaldehyde below the recommended exposure limits. Maintain adequate ventilation to prevent exposure above current OSHA / ACGIH exposure limits. Workplace monitoring of the air to define formaldehyde exposure levels may be necessary. This product contains trace amounts of acrylonitrile. It is exempt from the OSHA acrylonitrile standard 29 CFR 1910.1045, paragraph (a) (2) (ii). Acrylonitrile has been classified by IARC as possibly carcinogenic to humans, by OSHA as carcinogenic and by NTP as reasonably anticipated to be a human carcinogen.

## Section 12 - Ecological Information

**Ecological Information:** Ecological injuries are not known or expected under normal use.

## Section 13 - Disposal Information

**Disposal Information:** Dispose of material in accordance with all federal, state and local regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste.

**EPA Waste Code if Discarded (40 CFR Section 261):** None

## Section 14 - Transportation Information

|                                  |               |                          |      |
|----------------------------------|---------------|--------------------------|------|
| <b>DOT Proper Shipping Name:</b> | Not Regulated | <b>Packing Group:</b>    | N.A. |
| <b>DOT Technical Name:</b>       | N.A.          | <b>Hazard Subclass:</b>  | N.A. |
| <b>DOT Hazard Class:</b>         | N.A.          | <b>DOT UN/NA Number:</b> | N.A. |

Note: The shipping information provided is applicable for domestic ground transport only. Different categorization may apply if shipped via other modes of transportation and/or to non-domestic destinations.

## Section 15 - Regulatory Information

**CERCLA - SARA Hazard Category:**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Immediate Health Hazard, Chronic Health Hazard

**SARA Section 313:**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

None

**Toxic Substances Control Act:**

All ingredients in this product are either on TSCA inventory list, or otherwise exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

None

**U.S. State Regulations:****New Jersey Right-to-Know:**

The following materials are non-hazardous, but are among the top five components in this product:

| Chemical Name         | CAS Number  | WT%   |
|-----------------------|-------------|-------|
| Water                 | 7732 -18-5  | 10-30 |
| Non-Hazardous Polymer | Proprietary | 10-30 |

**Pennsylvania Right-to-Know:**

The following non-hazardous ingredients are present in the product at greater than 3%:

| Chemical Name         | CAS Number  | WT%   |
|-----------------------|-------------|-------|
| Water                 | 7732 -18-5  | 10-30 |
| Non-Hazardous Polymer | Proprietary | 10-30 |

**California Proposition 65:**

Warning: The following ingredients present in the product are known to the State of California to cause cancer:

| Chemical Name       | CAS Number | Definition    | Date Listed             | WT%       |
|---------------------|------------|---------------|-------------------------|-----------|
| Silica, crystalline | 14808-60-7 | Carcinogenic. | Listed: October 1, 1988 | 0.1-1.0   |
| Formaldehyde        | 50-00-0    | Carcinogenic. | Listed: January 1, 1988 | <0.02     |
| Ethyl acrylate      | 140-88-5   | Carcinogenic. | Listed: July 1, 1989    | <0.008    |
| Acetaldehyde        | 75-07-0    | Carcinogenic. | Listed: April 1, 1988   | <0.002    |
| Acrylonitrile       | 107-13-1   | Carcinogenic. | Listed: July 1, 1987    | <0.0002   |
| Acrylamide          | 79-06-1    | Carcinogenic. | Listed: January 1, 1990 | <0.00005  |
| Ethylene oxide      | 75-21-8    | Carcinogenic. | Listed: July 1, 1987    | <0.000006 |

Warning: The following ingredients present in the product are known to the State of California to cause birth defects or other reproductive harm:

| Chemical Name  | CAS Number | Definition | Date Listed               | WT%       |
|----------------|------------|------------|---------------------------|-----------|
| Ethylene oxide | 75-21-8    | Yes        | Listed: February 27, 1987 | <0.000006 |

**Section 16 - Other Information****HMIS Ratings:**

Health: 1      Flammability: 1      Reactivity: 0      Personal Protection: X

**VOLATILE ORGANIC COMPOUNDS**, GR/LTR: 59.2      LB/GAL: 0.5      WT%: 2.482

**REASON FOR REVISION:** Periodic Update

**Legend:**      N.A. – Not Applicable

ACGIH – American Conference of Governmental Industrial Hygienists

N.E. – Not Established

SARA – Superfund Amendments and Reauthorization Act of 1986

N.D. – Not Determined

NJRTK – New Jersey Right-to-Know Law

VOC – Volatile Organic Compound

OSHA – Occupational Safety and Health Administration

PEL – Permissible Exposure Limit

HMIS – Hazardous Materials Identification System

TLV – Threshold Limit Value

NTP – National Toxicology Program

STEL – Short Term Exposure Limit

CEIL – Ceiling Exposure Limit

LD50 – Lethal Dose 50

LC50 – Lethal Concentration 50

F – Degree Fahrenheit

C – Degree Celcius

MSDS – Material Safety Data Sheet

CASRN – The Chemical Abstracts Service Registry Number

DAP believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. **NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS.** Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.

&lt;End of MSDS&gt;