

MATERIAL SAFETY DATA SHEET

Chain and Cable Lubricant

Part number TY26350

MSDS NO.

TY26350

Revision Date:

05/16/2011

Date Printed

05/16/2011

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Common Name:

Chain and Cable Lubricant

Part number TY26350

Chemical Family:

Petroleum Oil Blend

Synonyms:

None

Emergency Telephone (24 hr.):

24-Hour Emergency Information: CHEMTREC (800) 424-9300

Manufacturer:

TIG Distributing, Inc, P.O. Box 535, Marshalltown, IA 50158, Phone Number 641-752-7876

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight %	OSHA TWA	OSHA STEL	OSHA SKIN
Butane 106-97-8	9-11	Not Listed	Not Listed	Not Listed
Heavy Hydrotreated Naphthenic Distillates (petroleum) 64742-52-5	58-62	Not Listed	Not Listed	Not Listed
Heavy Aliphatic Solvent Naphtha 64742-96-7	12-17	Not Listed	Not Listed	Not Listed
Propane 74-98-6	12-14	Not Listed	Not Listed	Not Listed
Hitec 511	1-5	Not Listed	Not Listed	Not Listed

Component	Weight %	OSHA Z PEL	OSHA Z TWA	OSHA Z Ceiling
Butane 106-97-8	9-11	Not Listed	1900 mg/m ³ 800 ppm	Not Listed
Heavy Hydrotreated Naphthenic Distillates (petroleum) 64742-52-5	58-62	2000 mg/m ³ 500 ppm	1600 mg/m ³ 400 ppm	Not Listed
Heavy Aliphatic Solvent Naphtha 64742-96-7	12-17	Not Listed	Not Listed	Not Listed
Propane 74-98-6	12-14	1800 mg/m ³ 1000 ppm	1800 mg/m ³ 1000 ppm	Not Listed
Hitec 511	1-5	Not Listed	Not Listed	Not Listed

MATERIAL SAFETY DATA SHEET

Chain and Cable Lubricant

Part number TY26350

MSDS NO.

TY26350

Revision Date:

05/16/2011

Date Printed

05/16/2011

Component	ACGIH TLV TWA	ACGIH TLV STEL	ACGIH TLV Ceiling
Butane 106-97-8	1000 ppm	Not Listed	Not Listed
Heavy Hydrotreated Naphthenic Distillates (petroleum) 64742-52-5	Not Listed	Not Listed	Not Listed
Heavy Aliphatic Solvent Naphtha 64742-96-7	Not Listed	Not Listed	Not Listed
Propane 74-98-6	1000 ppm	Not Listed	Not Listed
Hitec 511	Not Listed	Not Listed	Not Listed

3. HAZARDS IDENTIFICATION

Emergency Overview:

Content under pressure. Keep away from heat, sparks and flame. This material is a skin irritant.

HMIS Classification:

Health: 2 Flammability: 4 Physical Hazard: 2

NFPA Rating:

HEALTH 1, FLAMMABILITY 4, REACTIVITY 0

4. FIRST AID MEASURES

Eye Contact:

In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.

Ingestion:

If swallowed, do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to an unconscious person. Get medical attention! If vomiting occurs, keep head lower than hips to prevent aspiration.

Inhalation:

If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

Skin Contact:

Wash with soap and water for 15 minutes. If irritation persists or signs of toxicity occur, seek medical attention. Remove contaminated clothing and shoes, and launder before reuse.

5. FIRE FIGHTING MEASURES

Flammable Properties

Flash Point °F(°C):

<0 F (<-17.8 C)

Flash Point Method:

TAG Closed Cup

Flammable Limits in Air - Lower (%):

.9%

Flammable Limits in Air - Upper (%):

Not Determined

Autoignition Temperature °F(°C):

Not Determined

Extinguishing Media:

Carbon dioxide. Foam. Use water spray to keep containers cool that are exposed to heat or flames.

Protection Of Fire-Fighters:

Special Fire-Fighting Procedures:

Wear approved positive-pressure self-contained breathing apparatus and protective clothing.

Hazardous Combustion Products:

Carbon Dioxide. Carbon Monoxide.

Aerosol Comments:

NFPA Level 3 Aerosol

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Wear appropriate protective clothing and equipment to prevent skin and eye contact.

Spill Procedures:

Contain any liquid from leaking containers. Avoid all sources of ignition; heat, sparks and open flames.

Action to be taken if material is released or spilled: Do not puncture or incinerate container. Contents under pressure. Wear proper protective equipment as specified in the protective equipment section. Remove sources of ignition. Leaking containers should be removed to an isolated, well-ventilated area and transferred to other suitable containers. Wipe, scrape, or soak up in an inert material and put in a container intended for flammable materials for disposal.

Environmental Precautions:

Do not allow to enter sanitary drains, sewer or surface and subsurface waters. Keep out of lakes, ponds or streams.

MATERIAL SAFETY DATA SHEET

Chain and Cable Lubricant

Part number TY26350

MSDS NO. TY26350
Revision Date: 05/16/2011
Date Printed 05/16/2011

7. HANDLING AND STORAGE

Handling and Storage: Caution: Contents under pressure. Keep away from heat and open flame. Use only in a well ventilated area. Avoid breathing vapors, if exposed to high vapor concentration, leave area at once. Avoid contact with skin and eyes. Do not puncture, incinerate or store above 120 F. Exposure to high temperatures may cause bursting. DO NOT store in the passenger compartment of an automobile.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Use in a well ventilated area. Local exhaust ventilation as necessary to maintain exposures to within applicable limits.
Eyes: Chemical goggles; also wear a face shield if splashing hazard exists.
Skin Protection: Avoid skin contact. Wear protective clothing and gloves.
Respiratory Protection: Do not breath mist or vapor. Use in a well ventilated area. Appropriate respiratory protection shall be worn when applied engineering controls are not adequate to protect against inhalation exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Colorless to pale yellow liquid
Odor: HYDROCARBON ODOR
pH Value: Not Determined
Vapor Pressure: Not Determined
Vapor Density (Air=1): Not Determined
Boiling Point (°F): >300 F (>149 C)(liquid)
Melting/Freezing Point: Not determined.
Solubility in Water: MODERATE
Bulk Density at 20°C: Not Determined
Molecular Weight: Mixture
Specific Gravity (H2O=1): .76 @ 60 F (liquid)
Viscosity: Not Determined.
Evaporation Rate: Not Determined
VOC Content(%): 49.2%
Decomposition Temperature: Not Determined

10. STABILITY AND REACTIVITY

Chemical Stability: Stable under normal conditions of handling, use and transportation.
Conditions to Avoid: Keep away from heat, sparks and flame. Avoid any source of ignition. Do not expose to heat or store at temperatures above 120 F.
Materials to Avoid: Strong oxidizing agents.
Hazardous Decomposition Products: Carbon monoxide. Carbon dioxide. Oxides of carbon and nitrogen, AVOID extreme heat
Hazardous Polymerization: WILL NOT OCCUR

11. TOXICOLOGICAL INFORMATION

Toxicological Data:

MATERIAL SAFETY DATA SHEET

Chain and Cable Lubricant

Part number TY26350

MSDS NO.

TY26350

Revision Date:

05/16/2011

Date Printed

05/16/2011

Component	Route	Species	Dose
Butane 106-97-8	Inhalation	Rats	LC50, 658 gm/m ³ /4H
Heavy Hydrotreated Naphthenic Distillates (petroleum) 64742-52-5	NA	NA	Not known.
Heavy Aliphatic Solvent Naphtha 64742-96-7	Inhalation	Rats	Not known.
Propane 74-98-6	NA	NA	Not known.
Hitec 511	Inhalation	Rats	Not known.

Carcinogenicity:

Component	IARC	NTP	OSHA
Butane 106-97-8	Not Listed	Not Listed	Not Listed
Heavy Hydrotreated Naphthenic Distillates (petroleum) 64742-52-5	Not Listed	Not Listed	Not Listed
Heavy Aliphatic Solvent Naphtha 64742-96-7	Not Listed	Not Listed	Not Listed
Propane 74-98-6	Not Listed	Not Listed	Not Listed
Hitec 511	Not Listed	Not Listed	Not Listed

12. ECOLOGICAL INFORMATION

Remarks:

Ecological testing has not been conducted on this product.

13. DISPOSAL CONSIDERATION

Waste Classification:

Residues and spilled material are hazardous waste due to ignitability.

Waste Management:

Not determined.

Disposal Method:

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORTATION INFORMATION

U.S. DOT:

Proper Shipping Name:

CONSUMER COMMODITY

Hazard Class:

ORM-D

UN/NA Number:

not applicable

DOT Packing Group:

Not Applicable

IMDG:

Proper Shipping Name:

Aerosols

Hazard Class:

2

Hazard Subclass:

2.1

UN No.:

UN1950

Packing Group:

Not Applicable

Marine Pollutant:

No

MATERIAL SAFETY DATA SHEET**Chain and Cable Lubricant****Part number TY26350**

MSDS NO.

TY26350

Revision Date:

05/16/2011

Date Printed

05/16/2011

15. REGULATORY INFORMATION**US Federal Regulations:**

Component	SARA 313	SARA 302	TPQ	RQ
Butane 106-97-8	Not Listed	Not Listed	Not Listed	Not Listed
Heavy Hydrotreated Naphthenic Distillates (petroleum) 64742-52-5	Not Listed	Not Listed	Not Listed	Not Listed
Heavy Aliphatic Solvent Naphtha 64742-96-7	Not Listed	Not Listed	Not Listed	Not Listed
Propane 74-98-6	Not Listed	Not Listed	Not Listed	Not Listed
Hitec 511	Not Listed	Not Listed	Not Listed	Not Listed

US OSHA HEALTH CLASSIFICATION:

Hazardous per OSHA 29 CFR 1910.1200

SARA 311/312 Hazard Categories:

Not Determined.

State Regulations:

Component	California Prop. 65 Cancer list	California - Prop 65 Developmental Toxicity	California Prop. 65 Reproductive Female	California Prop. 65 Reproductive Male
Butane 106-97-8	Not Listed	Not Listed	Not Listed	Not Listed
Heavy Hydrotreated Naphthenic Distillates (petroleum) 64742-52-5	Not Listed	Not Listed	Not Listed	Not Listed
Heavy Aliphatic Solvent Naphtha 64742-96-7	Not Listed	Not Listed	Not Listed	Not Listed
Propane 74-98-6	Not Listed	Not Listed	Not Listed	Not Listed
Hitec 511	Not Listed	Not Listed	Not Listed	Not Listed

MATERIAL SAFETY DATA SHEET

Chain and Cable Lubricant

Part number TY26350

MSDS NO.

TY26350

Revision Date:

05/16/2011

Date Printed

05/16/2011

Component	New Jersey Right-to-Know List:
Butane 106-97-8	Substance no. 0273 Substance no. 2422 Substance no. 2423 Substance no. 2425 Substance no. 2426 Substance no. 2427 Substance no. 2428 Substance no. 2429 Substance no. 2430
Propane 74-98-6	Substance no. 2422 Substance no. 2423 Substance no. 2425 Substance no. 2426 Substance no. 2427 Substance no. 2428 Substance no. 2429 Substance no. 2430 Substance no. 1594

U.S. TSCA:

One or more components of this product is not listed on the TSCA Inventory.

Canadian Inventory:

One or more components of this product is not listed on the Canadian DSL or NDSL Inventory.

Consumer Product Safety Improvement Act of 2008 General Conformity Certification

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product container.

16. OTHER INFORMATION

General Notes:

Disclaimer:

Do not allow undiluted material or large quantities to reach groundwater, bodies of water or sewer system. The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.